



Declaration of Performance

FIRETEX M90/02

FIRETEX M90/02 Declaration of Performance Issue 4

1. Unique identification code of the product type:

FIRETEX M90/02.

2. Type, product or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):

See packaging for batch number. The batch number takes the form AA1234AA(1).

3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:

Reactive coating for the fire protection of structural steel.

4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5) :

Sherwin-Williams Protective & Marine Coatings
Tower Works
Kestor Street
Bolton
BL2 2AL
England

5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):

Sherwin Williams
Inver France SAS
2 Rue Jean Devaux
79102 Thouars
France

6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:

System 1.

7. In case of the declaration of performance concerning a construction product covered by a harmonised standard:

Not applicable.

8. In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:

Element Materials Technology Rotterdam B.V. Zekeringstraat 33, 1014 BV Amsterdam, Netherlands issued ETA-20/1225 on the basis of EAD350402-00-1106, performed initial type testing , inspection of manufacturing plant and factory production control , continuous surveillance of factory production control and audit testing of samples under system 1 and issued certificate of conformity 2812-CPR-GA5017.



Declaration of Performance

9. Declared performance:

Essential Characteristics	Performance	Harmonised Technical Specification
Reaction to Fire	Class b-s1, d0	EN 13501-1
Resistance to Fire	R15 – R120 between 350°C and 750°C	EN 13501-2
Dangerous Substances	None	EAD350402-00-1106 Clause 2.2.3
Environmental conditions	Passed exposure conditions Y Z2 and Z1	EAD350402-00-1106 Clause 2.2.4 and 2.2.5
Primer Compatibility	Two pack epoxy blast primer	EAD350402-00-1106 Clause 2.2.4 and 2.2.5
Topcoat Compatibility	Acrolon C137V2 Acrolon C237	EAD350402-00-1106 Clause 2.2.4 and 2.2.5

For characteristics not listed above, these are either not relevant or No Performance Determined.

Where pursuant to Article 37 or 38 the Specific Technical Documentation has been used, the requirements with which the product applies:

Not applicable.

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of Sherwin-Williams Protective & Marine Coatings by:

Simon J. Hallam
Technical Director
Bolton 23/12/2020