



Protective & Marine Coatings
Europe, Middle East, Africa & India

FIRETEX[®] M71V2
**Sheen top coat designed
for internal environments**

FIRETEX[®]

INTUMESCENT PASSIVE FIRE PROTECTION

FIRETEX[®] M71V2

Sheen top coat designed for internal environments

Sheen top coat



FIRETEX[®] M71V2 has been developed as a sheen top coat for the FIRETEX[®] FX Range of intumescent coatings, for internal environments.

- Provides protection when used in internal semi controlled conditions where condensation may occur.
- Used to maintain the appearance of FIRETEX[®] systems.



INTUMESCENT PASSIVE
FIRE PROTECTION

Technical information



Recommended use: Will provide protection for FIRETEX[®] range of intumescent coatings for the life of building in an internally dry controlled C1 environment and up to 20 years in an internal semi controlled environment for C2 categories (as defined in ISO 12944-2).

Endorsements ETAG 18-2.

Volume solids: 44% (ASTM-D2697-91).

VOC: 472g/litre.

Application: Airless spray, brush, conventional spray and roller.

WFT (µm): Typical 114.

DFT (µm): Typical 50.

Time to touch dry: 60mins @ 15°C, 45mins @ 23°C, 30mins @ 35°C.

Time to recoat: 4hrs @ 15°C, 4hrs @ 23°C, 4hrs @ 35°C.

Time to handle: Dependant on underlying intumescent coating.

The Sherwin-Williams Company

With over 150 years experience in the coatings industry we understand how critical it is that your investment gives you a quality, long term fire protection system, which performs in demanding environments.

The world class FIRETEX® range provides a smooth, hard finish that allows flexibility and creative exposure of structural steel surfaces in building design, whilst also providing essential protection of steelwork from 15-120 minutes.

Whether you specify FIRETEX® alone or in conjunction with our exceptional primers and top coats, you can be assured that you are selecting a passive fire protection system that has been researched, developed and tested to the highest international standards.

Speak to your Sherwin-Williams representative to get an estimate on your next project using our FIRETEX® intumescent materials.



INTUMESCENT PASSIVE
FIRE PROTECTION



To learn more, contact us

Europe, Middle East, Africa & India: +44 (0)1204 521771

North America: +1 800 524 5979

Asia: +8 621 5158 7798

sales.uk@sherwin.com

©2018 The Sherwin-Williams Company
Protective & Marine Coatings

01/18 EMEA0112/V05

TM is a registered trademark in one or more countries.

www.protectiveemea.sherwin-williams.com